

(Material) Safety Data Sheet

HEALTH * 1 FLAMMABILITY O PHYSICAL HAZARD O PERSONAL PROTECTION PERS

Section 1 - Product and Company Identification

Material Name • Residential Building Insulation - Sustainable Insulation™

MSDS No. ■ CT10144-7

Product Description • Fiber Glass Insulation.

Product Use • Acoustical & Thermal Insulation.

Synonyms ■ Basement Wall Insulation; Building Insulation (Unfaced & Kraft Faced); Commercial

Blanket; Commercial Board Insulation; EverTherm; EZR Fiber Glass Insulation™; Flame-Resistant Class A (PSK-25); Flame-Resistant Class A (PSK-25) Fiber Glass Building Insulation; Foil-Faced Building Insulation; Masonry Wall Batts; Noise

Reducer™ Sound Batts; SpeedyR™; UltraTherm® Blowing Insulation

Manufacturer • CertainTeed Corporation

750 E. Swedesford Road

P.O. Box 860Valley Forge, PA19482-0105

United States

www.certainteed.com/insulation

CertainTeed - EHS@saint-gobain.com

Telephone

General ■ 610-341-7000 **Emergency** ■ 800-527-3887

Preparation Date • 10/15/2004 Last Revision Date • 06/22/2012 Literature Code • 30-45-002

Key to abbreviations

‡ = HMIS is a registered trademark of the American Coatings Association

Section 2 - Hazards Identification

EMERGENCY OVERVIEW

DANGER

Causes eye irritation. Causes mild skin irritation. May cause cancer via Inhalation. May cause damage to organs through prolonged or repeated exposure.

Prevention Do not breathe dust, fume, gas, mist, vapours and/or spray. Wash thoroughly after handling. Do not handle until all safety

precautions have been read and understood. Use personal protective equipment as required.

Response IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. IF INHALED: If breathing is difficult, remove

victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention.

Storage/Disposal Store locked up. Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.



This product may cause temporary irritation to the upper respiratory system, eyes, and skin. Avoid inhalation, skin and eye contact as temporary irritation may occur. Wear appropriate personal protective equipment as described in Section 8.

Physical Form • Solid Color • Tan

Odor • Faint sweet odor.
OSHA • Irritant, Carcinogen





WHMIS

 Class D - Poisonous and Infectious Materials - Division 2 - Subdivision A, Class D -Poisonous and Infectious Materials - Division 2 - Subdivision B



EU GHS

None

- Specific Target Organ Toxicity Repeated Exposure Category 2, Skin Corrosion/Irritation - Category 3, Serious Eye Damage, Eye Irritation - Category 2B, Carcinogenicity - Category 1B
- Inhalation, Skin, Eye, Ingestion/Oral
- Skin/Dermal, Lungs
- Skin/Dermal, Lungs

Route Of Entry
Target Organs
Medical Conditions
Aggravated by Exposure

Potential Health Effects Inhalation

Acute (Immediate)
Chronic (Delayed)

Skin

Acute (Immediate) Chronic (Delayed)

Eye

Acute (Immediate)

Chronic (Delayed)
Ingestion
Acute (Immediate)
Chronic (Delayed)

Carcinogenic Effects

- The dust from this material may cause respiratory irritation.
- Fiber glass wool is a possible cancer hazard. Fiber glass wool has caused cancer in animals but has not produced cancer by inhalation in humans. Use of these products has not been shown to cause cancer in humans.
- May cause irritation.
- No data available.
- Contact with the eyes may cause irritation due to the abrasive action of the dust. Not
 expected to cause prolonged or significant eye irritation. Material is dusty and may
 scratch the surface of the eye.
- No data available.
- Unlikely. Contact physician if unusual reaction is noted.
- No data available.
 - This product contains glass wool insulation fibers. Following a thorough review of all the medical-scientific data available at a meeting in October 2001, the IARC panel lowered the classification for glass wool insulation fibers from a Group 2B classification ("possibly carcinogenic to humans") to a Group 3 classification ("not classifiable as to carcinogenicity to humans"). According to IARC, there is "no evidence of increased risks of lung cancer or of mesothelioma from occupational exposures during manufacturing of these materials, and inadequate evidence overall of any cancer risk." This product contains petroleum asphalt. Asphalt fumes arise from hot asphalt. Asphalt fumes (CAS # 8052-42-4): In 1985/87, IARC (International Agency for Research on Cancer) concluded the following: (a) Bitumens are not classifiable as to their carcinogenicity to humans (Group 3). (b) Extracts of steam- and air-refined bitumens are possibly carcinogenic to humans (Group 2B). IARC found that evidence for carcinogenicity from animal studies was: inadequate for undiluted airrefined bitumens; limited for steam-refined and cracking residue bitumens; sufficient for extracts of steam-refined and air-refined bitumen. IARC found that human evidence for carcinogenicity of asphalt fumes was inadequate. Studies of roofers indicated an excess of cancers; however, IARC concluded that, since roofers may be exposed also to coal-tar pitches and other materials, "the excess cancer risk cannot be attributed specifically to bitumens." In 1994, a published review of 20 epidemiology studies of asphalt workers and roofers agreed with IARC, that current human evidence is inadequate for the carcinogenicity of asphalt fumes in humans. Trace amounts of polynuclear aromatic hydrocarbons (PAHs) may be present in some asphalts and can be released upon excessive heating, which results in thermal



cracking of the asphalt compounds. Some of these PAHs have been identified as having the potential to induce carcinogenic and reproductive health effects.

		Carcinogenic Effects	
	CAS	IARC	NTP
Asphalt	8052-42-4	Group 2B-Possible Carcinogen	Not Established
Acetic acid, vinyl ester, polymer	9003-20-7	Group 3-Not Classifiable	Not Established
Glass, oxide, chemicals as Glass wool fiber	NDA	Group 3-Not Classifiable	Reasonably Anticipated to be Human Carcinogen

Other Information

 Hearing Conservation: Some blowing machines used to install blown-in products create elevated sound levels which may affect workers' hearing. Use of hearing protection by workers exposed above 85 dB(A) as an 8-hour TWA is recommended.

See Section 12 for Ecological Information.

Section 3 - Composition/Information on Ingredients

		Hazardou	s Components	3		
Chemical Name	CAS	%(wt)	UN;EINECS	LD50/LC50	EU R & S Phrases	Other
Glass, oxide, chemicals	65997-17- 3	78% TO 97%		NDA	NDA	NDA
Asphalt	8052-42-4	0% TO 17%	NA1999, 232- 490-9	Ingestion/Oral-Rat LD50 · >5000 mg/kgInhalation-Rat LC50 · >94.4 mg/m³	NDA	NDA
Proprietary	Proprietary	3% TO 9%	Proprietary	NDA	NDA	NDA
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54- 7	0.5% TO 1.5%	265-157-1	NDA	Carc.Cat.2; R45	NDA
	Ne	on-Hazard	ous Componei	nts		
Chemical Name	CAS	%(wt)	UN;EINECS	LD50/LC50	EU R & S Phrases	Other
Mineral oil, petroleum distillates, solvent- dewaxed heavy paraffinic (severe solvent- refiningand/or hydrotreatment)	64742-65- 0	0.5% TO 1.5%	265-169-7	NDA	Carc.Cat.2; R45	NDA
Acetic acid, vinyl ester, polymer	9003-20-7	< 11%	NDA	Ingestion/Oral-Rat LD50 · >25 g/kg	NDA	NDA
Acetic acid ethenyl ester, polymer with ethene	24937-78- 8	< 7%	NDA	Ingestion/Oral-Rat LD50 · >2500 mg/kg	NDA	NDA

Under United States Regulations (29 CFR 1900.1200 - Hazard Communication Standard), this product is considered hazardous. In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS). According to the Globally Harmonized Standard for Classification and Labeling (GHS) this product is considered hazardous.

See Section 11 for Toxicological Information.

Section 4 - First Aid Measures

Inhalation Skin

- Remove to fresh air immediately and notify medical personnel and supervisor.
- After contact with skin, take off immediately all contaminated clothing and wash immediately with plenty of soap and water. If irritation develops and persists, get medical attention.
- Do no rub or scratch your eyes. Immediately flush eyes with plenty of water for at

Eye



Ingestion

Hazards

least 15 minutes and notify medical personnel and supervisor.

Unlikely. Consult physician if unusual reaction is noted.

See Section 2 for Potential Health Effects.

Section 5 - Fire Fighting Measures

Extinguishing Media
Unsuitable Extinguishing
Media
Firefighting Procedures

- Use that which is applicable to surrounding fire.
- None known.

Unusual Fire and Explosion

 Fire fighters should avoid inhaling any combustion products. Firefighters should wear full-face, self contained breathing apparatus and impervious protective clothing.

Hazardous Combustion Products

Does not support combustion. These products contain a cured binder and various facings which contain retardant systems to reduce the possibility of fire. Use of plasma or other type of cutting tool may cause the release of toxic fumes and smoke. Facings on these products may burn. Do not leave facing exposed when working close to an open flame. If burned, the materials could release toxic fumes.

• If burned, the materials could release toxic fumes and smoke. The binder and kraft facings combustion products include carbon-dioxide, hydrogen chloride, carbon monoxide and molecular fragments of hydrocarbon particles, carbon-hydrogen-nitrogen and nitrogen-oxygen compounds. Comparative animal inhalation toxicity studies of combustion products on a number of CertainTeed fiber glass insulation products found the insulation products to be no more toxic than wood based on incapacitation and mortality.

Protection of Firefighters

Wear full structural fire fighting protective clothing.

Section 6 - Accidental Release Measures

Personal Precautions Emergency Procedures

- Avoid contact with skin and eyes during clean-up.
- Persons not wearing appropriate protective equipment should be excluded from area of spill until clean-up has been completed. Ventilate the contaminated area.

Environmental Precautions Containment/Clean-up Measures Prohibited Materials

- No data available
- Vacuum dust deposits. Do not use compressed air for clean-up. Avoid generating dust
- None known.
 No data available.

Section 7 - Handling and Storage

Handling

Do not breathe dust from this material. Keep this product from heat, sparks, or open flame. Use this product with adequate ventilation. Always wash work clothes separately from other clothing. Wipe out the washer or sink to prevent loose glass fibers from getting on other clothing. Wash thoroughly after handling. Use personal protective equipment as described in Section 8.

Storage
Special Packaging Materials
Incompatible Materials or
Ignition Sources
Other Information

- Store in a dry place and under cover to protect product.
- None known.
- None known.
- No data available.



Section 8 - Exposure Controls/Personal Protection

Personal Protective Equipment

Pictograms







Respiratory

• Wear NIOSH-certified respirators when handling and applying fiber glass insulation products in accordance with established exposure guidelines - If the exposure is less than 10 times the exposure guild line wear 1/2 mask respirator, N95 or higher, such as 3M brand #8210, #8511 or #8233. If the exposure is less than 50 times the exposure guideline wear a full face respirator, N100 or higher, such as 3M brand 6000 or 7000 series.

Eye/Face

 Safety glasses with side shields should be worn at a minimum. In dusty environments chemical goggles should be worn.

Hands

 Work clothing sufficient to prevent all skin contact should be worn, such as overalls, long sleeves and cap.

Skin/Body

 No skin protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid skin contact.

General Industrial Hygiene Considerations

 Wash hands, face and other potentially exposed areas immediately after handling material (especially before eating, drinking, or smoking). Decontaminate all protective equipment after use.

Engineering Measures/Controls

 Avoid spread of fiber glass dust. Provide general and/or local exhaust ventilation to control airborne dust levels below exposure limits.

			Exposure Limits/Guidel	lines	
	Result	ACGIH	Mexico	NIOSH	United States - California
	STELs	Not established	10 mg/m3 STEL	Not established	Not established
Asphalt (8052-42-4)	TWAs	0.5 mg/m3 TWA (as benzene soluble aerosol, fume, inhalable fraction)	5 mg/m3 TWA	Not established	5 mg/m3 PEL (fume)
4)	Ceiling s	Not established	Not established	5 mg/m3 Ceiling (fume, 15 min)	Not established
Glass, oxide, chemical s as Glass wool fiber	TWAs	1 fiber/cm3 TWA (respirable fibers: length >5 µm, aspect ratio >=3:1, as determined by the membrane filter method at 400-450X magnification [4-mm objective], using phase-contrast illumination) as Glass wool fiber	Not established	3 fibers/cm3 TWA (fibers <= 3.5 μm in diameter and >= 10 μm in length); 5 mg/m3 TWA (total) as Glass wool fiber	10 mg/m3 PEL (total dust); 5 mg/m3 PEL (respirable fraction) as Glass wool fiber

Exposure Control Notations

Mexico

- Asphalt (8052-42-4): Carcinogens: A4 - Not classifiable as a human carcinogen

ACGIH

- Asphalt (8052-42-4): Carcinogens: A4 Not Classifiable as a Human Carcinogen (fume, coal tar-free)
- Glass, oxide, chemicals as Glass wool fiber: Carcinogens: A3 Confirmed Animal Carcinogen with Unknown Relevance to Humans

Exposure Limits Supplemental ACGIH



Exposure Limits Supplemental

• Asphalt (8052-42-4):BEIs:Medium: urine Time: end of shift at end of workweek Parameter: 1-Hydroxypyrene with hydrolysis (nonquantitative)| TLV Basis - Critical Effects:eye and upper respiratory tract irritation (fume)

Section 9 - Physical and Chemical Properties

Physical Form

Appearance/Description

- Solid
- Fibers assembled into blankets or loose fill. The blankets may be faced with kraft, aluminum foil or other facings.

Color: Tan		Odor: Faint sweet odor.	
Taste: No data available.		Odor Threshold: NDA	
Boiling Point:	NDA	Vapor Pressure:	NDA
Melting Point:	2200 F(1204.4444 C)	Vapor Density:	NDA
Specific Gravity:	2.5	Evaporation Rate:	NDA
Density:	0.51 - 1.34 lb(s)/ft ³	VOC (Wt.):	NDA
Bulk Density:	NDA	VOC (Vol.):	NDA
pH:	NDA	Volatiles (Wt.):	NDA
Water Solubility:	Slightly Soluble	Volatiles (Vol.):	NDA
Solvent Solubility:	NDA	Flash Point:	NDA
Viscosity:	NDA	Flash Point Test Type:	NDA
Half-Life:	NDA	UEL:	NDA
Octanol/Water Partition coefficient:	NDA	LEL:	NDA
Coefficient of water/oil distribution:	NDA	Autoignition:	NDA
Bioaccumulation Factor:	NDA	Bioconcentration Factor:	NDA
Biochemical Oxygen Demand BOD/BOD5:	NDA	Chemical Oxygen Demand:	NDA
Persistence:	NDA	Degradation:	NDA

Section 10 - Stability and Reactivity

Stability

Hazardous Polymerization Conditions to Avoid Incompatible Materials Hazardous Decomposition Products

- Stable under normal conditions of use.
- Hazardous polymerization not indicated.
- Keep away from heat, ignition sources and incompatible materials.
- Hydrofluoric acid.
- Hazardous decomposition may occur generating toxic fumes/vapors, oxides of carbon (COx), oxides of nitrogen (NOx).
 No data available.

NO data available

Section 11 - Toxicological Information

Temporary irritation may be observed in the upper respiratory system, eyes, and skin. This product has not been tested as a separate entity. Therefore, the hazards must be evaluated on the basis of the individual ingredients, and those hazards must be assumed to be additive in the absence of complete information.

Component Name	Concentration	CAS	Data
Acetic acid, vinyl ester, polymer	< 11%	9003-20-7	Acute Toxicity: ; orl-rat LD50:>25 gm/kg
Acetic acid ethenyl ester, polymer with	< 7%	24937-78-	Acute Toxicity: ; Ingestion/Oral-Rat LD50 · >2500 mg/kg



Component Name	Concentration	CAS	Data
ethene		8	
Glass, oxide, chemicals	78% TO 97%	65997-17- 3	Acute Toxicity: ; ihl-ham TCLo:30 mg/m3/6H/13W-I; ihl-ham TCLo:30 mg/m3/6H/78W-I; ihl-rat TCLo:16 mg/m3/6H/13W-I Mutagen: ; mnt-ham:lng 2 ug/cm2; oms-ham:ovr 10 mg/L; oms-hmn:fbr 10 mg/L Tumorigen/Carcinogen: ; imp-rat TDLo:200 mg/kg
Asphalt	0% TO 17%	8052-42-4	Acute Toxicity: ; orl-rat LD50:>5000 mg/kg; ihl-rat LC50:>94.4 mg/m3; ihl-rat TCLo:100 mg/m3/6H/14W-l

Following a thorough review of all of the medical-scientific data available at a meeting in October 2001, the IARC panel lowered the classification for glass wool insulation fibers from a Group 2B classification ("possibly carcinogenic to humans") to a Group 3 classification ("not classifiable as to carcinogenicity to humans"). According to IARC, there is "no evidence of increased risks of lung cancer or of mesothelioma...from occupational exposures during the manufacture of these materials, and inadequate evidence overall of any cancer risk."

Key to abbreviations

TC = Toxic Concentration
LD = Lethal Dose

Section 12 - Ecological Information

Ecological Fate Persistence/Degradability

- No data available.
- Binder-coated fiber glass is hydrophobic, therefore, no adverse environmental
 effects would be expected if this product were accidentally released in the water or
 soil. No harm to fish or wildlife would be caused by this product.

Bioaccumulation Potential Mobility in Soil

- No data available.
- Binder-coated fiber glass is hydrophobic, therefore, no adverse environmental
 effects would be expected if this product were accidentally released in the water or
 soil. No harm to fish or wildlife would be caused by this product.

This product is not manufactured with, nor does it contain any Class I Ozone depleting chemicals as defined by EPA in Title VI of the Clean Air Act Amendments of 1990 40 CFR Part 82, Protection of Stratospheric Ozone. This product is not classified as a hazardous air pollutant in Title III Clean Air Act of 1990. CertainTeed's residential fiber glass insulation batts meet GREENGUARD Emission Standards. CertainTeed's certification confirms compliance with GREENGUARD Emission Standards, which are based on criteria used by the State of Washington, the U.S. Environmental Protection Agency (EPA), OSHA and the World Health Organization for total particulate and Volatile Organic Compounds (VOC) emissions, including formaldehyde. Additionally, CertainTeed's residential fiber glass insulation products meet the following emission criteria: California Section CA1350 material specification for schools and offices; OSHA Purchase Specification; State of Washington; EPA; and Proposed State of California. CertainTeed's residential fiber glass insulations also meet the EPA Recovered Material Guideline for recycled content.

Section 13 - Disposal Considerations

Product

 Dispose of waste material in an approved landfill in accordance with federal, state, and local regulations. If you are unsure of the regulations, contact your Public Health Department, or the local office of the Environmental Protection Agency (EPA). See Section 7 for Handling Procedures; see Section 8 for Personal Protective Equipment recommendations.

Packaging

No data available.
 No data available.

Section 14 - Transportation Information



DOT - United States - Department of Transportation Shipping Name:Not Regulated

TDG - Canada - Transport of Dangerous Goods Shipping Name:Not Regulated

IMO/IMDG –International Maritime Transport Shipping Name:Not Regulated

Section 15 - Regulatory Information

SARA Hazard Classifications

Acute, Chronic

		State Right To Know		
Component	CAS	MA	NJ	PA
Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment)	64742-65-0	No	No	No
Acetic acid, vinyl ester, polymer	9003-20-7	No	No	No
Acetic acid ethenyl ester, polymer with ethene	24937-78-8	No	No	No
Glass, oxide, chemicals	65997-17-3	Yes	No	Yes
Asphalt	8052-42-4	Yes	Yes	Yes
Proprietary	NDA	No	No	No
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	No	No	No

		Inventory		
Component	CAS	Canada DSL	Canada NDSL	TSCA
Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment)	64742-65-0	Yes	No	Yes
Acetic acid, vinyl ester, polymer	9003-20-7	Yes	No	Yes
Acetic acid ethenyl ester, polymer with ethene	24937-78-8	Yes	No	Yes
Glass, oxide, chemicals	65997-17-3	Yes	No	Yes
Asphalt	8052-42-4	Yes	No	Yes
Proprietary	NDA	No	No	No
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	Yes	No	Yes

Canada

Labor			
Canada - WHMIS - Classifications of Substances			
Glass, oxide, chemicals as Glass wool fiber		78% TO 97%	Uncontrolled product according to WHMIS classification criteria; D2A
Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment)	64742-65-0	0.5% TO 1.5%	Not Listed
Acetic acid ethenyl ester, polymer with ethene	24937-78-8	< 7%	Not Listed



Asphalt	8052-42-4	0% TO 17%	Not Listed
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	0.5% TO 1.5%	Not Listed
Acetic acid, vinyl ester, polymer	9003-20-7	< 11%	Not Listed
Glass, oxide, chemicals		78% TO 97%	Uncontrolled product according to WHMIS classification criteria; D2A
Canada - WHMIS - Ingredient Disclosure List			
Glass, oxide, chemicals as Glass wool fiber		78% TO 97%	Not Listed
• Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment)	64742-65-0	0.5% TO 1.5%	Not Listed
 Acetic acid ethenyl ester, polymer with ethene 	24937-78-8	< 7%	Not Listed
 Asphalt 	8052-42-4	0% TO 17%	Not Listed
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	0.5% TO 1.5%	Not Listed
 Acetic acid, vinyl ester, polymer 	9003-20-7	< 11%	Not Listed
Glass, oxide, chemicals	65997-17-3	78% TO 97%	Not Listed
Environment			
Canada - CEPA - Priority Substances List			
Glass, oxide, chemicals as Glass wool fiber		78% TO 97%	Not Listed
Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment)	64742-65-0	0.5% TO 1.5%	Not Listed
 Acetic acid ethenyl ester, polymer with ethene 	24937-78-8	< 7%	Not Listed
 Asphalt 	8052-42-4	0% TO 17%	Not Listed
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	0.5% TO 1.5%	Not Listed
 Acetic acid, vinyl ester, polymer 	9003-20-7	< 11%	Not Listed

Canada British Columbia

• Glass, oxide, chemicals

Environment			
Canada - British Columbia - Ozone Depleting Substances			
Glass, oxide, chemicals as Glass wool fiber		78% TO 97%	Not Listed
 Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment) 	64742-65-0	0.5% TO 1.5%	Not Listed
 Acetic acid ethenyl ester, polymer with ethene 	24937-78-8	< 7%	Not Listed
- Asphalt	8052-42-4	0% TO 17%	Not Listed
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	0.5% TO 1.5%	Not Listed
 Acetic acid, vinyl ester, polymer 	9003-20-7	< 11%	Not Listed
Glass, oxide, chemicals	65997-17-3	78% TO 97%	Not Listed

65997-17-3

78% TO 97% Not Listed

Canada Manitoba

Environment			
Canada - Manitoba - Ozone Depleting Substances and Other Haloca	rbons - Class 1		
Glass, oxide, chemicals as Glass wool fiber		78% TO 97%	Not Listed
Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment)	64742-65-0	0.5% TO 1.5%	Not Listed
Acetic acid ethenyl ester, polymer with ethene	24937-78-8	< 7%	Not Listed



- Asphalt	8052-42-4	0% TO 17%	Not Listed
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	0.5% TO 1.5%	Not Listed
Acetic acid, vinyl ester, polymer	9003-20-7	< 11%	Not Listed
Glass, oxide, chemicals	65997-17-3	78% TO 97%	Not Listed
Canada - Manitoba - Ozone Depleting Substances and Other Halocal	rbons - Class 2		
Glass, oxide, chemicals as Glass wool fiber		78% TO 97%	Not Listed
 Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment) 	64742-65-0	0.5% TO 1.5%	Not Listed
 Acetic acid ethenyl ester, polymer with ethene 	24937-78-8	< 7%	Not Listed
 Asphalt 	8052-42-4	0% TO 17%	Not Listed
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	0.5% TO 1.5%	Not Listed
Acetic acid, vinyl ester, polymer	9003-20-7	< 11%	Not Listed
Glass, oxide, chemicals	65997-17-3	78% TO 97%	Not Listed

Canada Nova Scotia

Environment			
Canada - Nova Scotia - Ozone Layer Protection Regulations			
Glass, oxide, chemicals as Glass wool fiber		78% TO 97%	Not Listed
 Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment) 	64742-65-0	0.5% TO 1.5%	Not Listed
Acetic acid ethenyl ester, polymer with ethene	24937-78-8	< 7%	Not Listed
- Asphalt	8052-42-4	0% TO 17%	Not Listed
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	0.5% TO 1.5%	Not Listed
 Acetic acid, vinyl ester, polymer 	9003-20-7	< 11%	Not Listed
Glass, oxide, chemicals	65997-17-3	78% TO 97%	Not Listed

Canada Ontario

Environment			
Canada - Ontario - Airborne Contaminant Reporting - Table 2A			
Glass, oxide, chemicals as Glass wool fiber		78% TO 97%	Not Listed
Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment)	64742-65-0	0.5% TO 1.5%	Not Listed
 Acetic acid ethenyl ester, polymer with ethene 	24937-78-8	< 7%	Not Listed
 Asphalt 	8052-42-4	0% TO 17%	Not Listed
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	0.5% TO 1.5%	Not Listed
 Acetic acid, vinyl ester, polymer 	9003-20-7	< 11%	Not Listed
Glass, oxide, chemicals	65997-17-3	78% TO 97%	Not Listed
Canada - Ontario - Airborne Contaminant Reporting - Table 2B			
Glass, oxide, chemicals as Glass wool fiber		78% TO 97%	Not Listed
• Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment)	64742-65-0	0.5% TO 1.5%	Not Listed
 Acetic acid ethenyl ester, polymer with ethene 	24937-78-8	< 7%	Not Listed
 Asphalt 	8052-42-4	0% TO 17%	Not Listed
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	0.5% TO	Not Listed



		1.5%	
 Acetic acid, vinyl ester, polymer 	9003-20-7	< 11%	Not Listed
Glass, oxide, chemicals	65997-17-3	78% TO 97%	Not Listed
Canada - Ontario - Ozone Depleting Substances - Solvents - Class 1			
Glass, oxide, chemicals as Glass wool fiber		78% TO 97%	Not Listed
 Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment) 	64742-65-0	0.5% TO 1.5%	Not Listed
 Acetic acid ethenyl ester, polymer with ethene 	24937-78-8	< 7%	Not Listed
Asphalt	8052-42-4	0% TO 17%	Not Listed
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	0.5% TO 1.5%	Not Listed
Acetic acid, vinyl ester, polymer	9003-20-7	< 11%	Not Listed
Glass, oxide, chemicals	65997-17-3	78% TO 97%	Not Listed
Canada - Ontario - Ozone Depleting Substances - Solvents - Class 2			
 Glass, oxide, chemicals as Glass wool fiber 		78% TO 97%	Not Listed
Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment)	64742-65-0	0.5% TO 1.5%	Not Listed
Acetic acid ethenyl ester, polymer with ethene	24937-78-8	< 7%	Not Listed
 Asphalt 	8052-42-4	0% TO 17%	Not Listed
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	0.5% TO 1.5%	Not Listed
Acetic acid, vinyl ester, polymer	9003-20-7	< 11%	Not Listed
Glass, oxide, chemicals	65997-17-3	78% TO 97%	Not Listed
Canada - Ontario - Ozone Depleting Substances - Solvents - Class 3			
Glass, oxide, chemicals as Glass wool fiber		78% TO 97%	Not Listed
 Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment) 	64742-65-0	0.5% TO 1.5%	Not Listed
 Acetic acid ethenyl ester, polymer with ethene 	24937-78-8	< 7%	Not Listed
Asphalt	8052-42-4	0% TO 17%	Not Listed
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	0.5% TO 1.5%	Not Listed
Acetic acid, vinyl ester, polymer	9003-20-7	< 11%	Not Listed
Glass, oxide, chemicals	65997-17-3	78% TO 97%	Not Listed

Canada Yukon

Environment					
Canada - Yukon - Ozone Depleting Substances and Other Halocarbons					
Glass, oxide, chemicals as Glass wool fiber		78% TO 97%	Not Listed		
Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment)	64742-65-0	0.5% TO 1.5%	Not Listed		
Acetic acid ethenyl ester, polymer with ethene	24937-78-8	< 7%	Not Listed		
Asphalt	8052-42-4	0% TO 17%	Not Listed		
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	0.5% TO 1.5%	Not Listed		
Acetic acid, vinyl ester, polymer	9003-20-7	< 11%	Not Listed		
Glass, oxide, chemicals	65997-17-3	78% TO 97%	Not Listed		

Mexico



Other			
Mexico - Hazard Classifications			
Glass, oxide, chemicals as Glass wool fiber		78% TO 97%	Not Listed
 Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment) 	64742-65-0	0.5% TO 1.5%	Not Listed
 Acetic acid ethenyl ester, polymer with ethene 	24937-78-8	< 7%	Not Listed
 Asphalt 	8052-42-4	0% TO 17%	Not Listed
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	0.5% TO 1.5%	Not Listed
 Acetic acid, vinyl ester, polymer 	9003-20-7	< 11%	Not Listed
 Glass, oxide, chemicals 	65997-17-3	78% TO 97%	Not Listed
Mexico - Regulated Substances			
 Glass, oxide, chemicals as Glass wool fiber 		78% TO 97%	Not Listed
 Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment) 	64742-65-0	0.5% TO 1.5%	Not Listed
 Acetic acid ethenyl ester, polymer with ethene 	24937-78-8	< 7%	Not Listed
 Asphalt 	8052-42-4	0% TO 17%	Not Listed
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	0.5% TO 1.5%	Not Listed
Acetic acid, vinyl ester, polymer	9003-20-7	< 11%	Not Listed
Glass, oxide, chemicals	65997-17-3	78% TO 97%	Not Listed

United States

Labor			
U.S OSHA - Process Safety Management - Highly Hazardous Chen	nicals		
Glass, oxide, chemicals as Glass wool fiber		78% TO 97%	Not Listed
 Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment) 	64742-65-0	0.5% TO 1.5%	Not Listed
 Acetic acid ethenyl ester, polymer with ethene 	24937-78-8	< 7%	Not Listed
 Asphalt 	8052-42-4	0% TO 17%	Not Listed
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	0.5% TO 1.5%	Not Listed
 Acetic acid, vinyl ester, polymer 	9003-20-7	< 11%	Not Listed
 Glass, oxide, chemicals 	65997-17-3	78% TO 97%	Not Listed
J.S OSHA - Specifically Regulated Chemicals			
Glass, oxide, chemicals as Glass wool fiber		78% TO 97%	Not Listed
 Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment) 	64742-65-0	0.5% TO 1.5%	Not Listed
 Acetic acid ethenyl ester, polymer with ethene 	24937-78-8	< 7%	Not Listed
 Asphalt 	8052-42-4	0% TO 17%	Not Listed
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	0.5% TO 1.5%	Not Listed
Acetic acid, vinyl ester, polymer	9003-20-7	< 11%	Not Listed
 Glass, oxide, chemicals 	65997-17-3	78% TO 97%	Not Listed

Environment

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants

Glass, oxide, chemicals as Glass wool fiber
 78% TO (includes mineral fiber emissions from facilities



		97%		rocessing glass, rock, or slag fibers [or ed fibers] of average diameter 1 µm or less)
Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment)	64742-65-0	0.5% TO 1.5%	Not Listed	
 Acetic acid ethenyl ester, polymer with ethene 	24937-78-8	< 7%	Not Listed	
Asphalt	8052-42-4	0% TO 17%	Not Listed	
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	0.5% TO 1.5%	Not Listed	
 Acetic acid, vinyl ester, polymer 	9003-20-7	< 11%	Not Listed	
Glass, oxide, chemicals		78% TO 97%	manufacturing or pr	oer emissions from facilities occessing glass, rock, or slag fibers [or other ors] of average diameter 1 µm or less)
U.S CERCLA/SARA - Hazardous Substances and	their Reportable	Quantities		
Glass, oxide, chemicals as Glass wool fiber			78% TO 97%	Not Listed
Mineral oil, petroleum distillates, solvent-dewaxed he (severe solvent-refiningand/or hydrotreatment)	eavy paraffinic	64742-65-0	0.5% TO 1.5%	Not Listed
 Acetic acid ethenyl ester, polymer with ethene 		24937-78-8	< 7%	Not Listed
Asphalt		8052-42-4	0% TO 17%	Not Listed
Hydrotreated heavy paraffinic petroleum distillate (high	ghly refined)	64742-54-7	0.5% TO 1.5%	Not Listed
 Acetic acid, vinyl ester, polymer 		9003-20-7	< 11%	Not Listed
Glass, oxide, chemicals		65997-17-3	78% TO 97%	Not Listed
U.S CERCLA/SARA - Radionuclides and Their Rep	oortable Quantit	ies		
Glass, oxide, chemicals as Glass wool fiber			78% TO 97%	Not Listed
Mineral oil, petroleum distillates, solvent-dewaxed he (severe solvent-refiningand/or hydrotreatment)	eavy paraffinic	64742-65-0	0.5% TO 1.5%	Not Listed
Acetic acid ethenyl ester, polymer with ethene		24937-78-8	< 7%	Not Listed
Asphalt		8052-42-4	0% TO 17%	Not Listed
Hydrotreated heavy paraffinic petroleum distillate (high	ghly refined)	64742-54-7	0.5% TO 1.5%	Not Listed
Acetic acid, vinyl ester, polymer		9003-20-7	< 11%	Not Listed
Glass, oxide, chemicals		65997-17-3	78% TO 97%	Not Listed

United States - California

Environment			
U.S California - Proposition 65 - Carcinogens List			
Glass, oxide, chemicals as Glass wool fiber		78% TO 97%	carcinogen, initial date 7/1/90 (airborne particles of respirable size)
Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment)	64742-65-0	0.5% TO 1.5%	Not Listed
Acetic acid ethenyl ester, polymer with ethene	24937-78-8	< 7%	Not Listed
Asphalt	8052-42-4	0% TO 17%	Not Listed
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	0.5% TO 1.5%	Not Listed
Acetic acid, vinyl ester, polymer	9003-20-7	< 11%	Not Listed
Glass, oxide, chemicals		78% TO 97%	carcinogen, initial date 7/1/90 (airborne particles of respirable size)



Glass, oxide, chemicals as Glass wool fiber		78% TO 97%	Not Listed
• Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment)	64742-65-0	0.5% TO 1.5%	Not Listed
 Acetic acid ethenyl ester, polymer with ethene 	24937-78-8	< 7%	Not Listed
Asphalt	8052-42-4	0% TO 17%	Not Listed
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	0.5% TO 1.5%	Not Listed
Acetic acid, vinyl ester, polymer	9003-20-7	< 11%	Not Listed
Glass, oxide, chemicals	65997-17-3	78% TO 97%	Not Listed
U.S California - Proposition 65 - Reproductive Toxicity - Female			
Glass, oxide, chemicals as Glass wool fiber		78% TO 97%	Not Listed
 Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment) 	64742-65-0	0.5% TO 1.5%	Not Listed
 Acetic acid ethenyl ester, polymer with ethene 	24937-78-8	< 7%	Not Listed
 Asphalt 	8052-42-4	0% TO 17%	Not Listed
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	0.5% TO 1.5%	Not Listed
 Acetic acid, vinyl ester, polymer 	9003-20-7	< 11%	Not Listed
Glass, oxide, chemicals	65997-17-3	78% TO 97%	Not Listed
J.S California - Proposition 65 - Reproductive Toxicity - Male			
Glass, oxide, chemicals as Glass wool fiber		78% TO 97%	Not Listed
 Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment) 	64742-65-0	0.5% TO 1.5%	Not Listed
 Acetic acid ethenyl ester, polymer with ethene 	24937-78-8	< 7%	Not Listed
 Asphalt 	8052-42-4	0% TO 17%	Not Listed
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	0.5% TO 1.5%	Not Listed
 Acetic acid, vinyl ester, polymer 	9003-20-7	< 11%	Not Listed
Glass, oxide, chemicals	65997-17-3	78% TO 97%	Not Listed

United States - Massachusetts

United States - New Jersey

United States - Pennsylvania

Labor			
U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard L	ist		
Glass, oxide, chemicals as Glass wool fiber		78% TO 97%	Not Listed
• Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment)	64742-65-0	0.5% TO 1.5%	Not Listed
 Acetic acid ethenyl ester, polymer with ethene 	24937-78-8	< 7%	Not Listed
Asphalt	8052-42-4	0% TO 17%	Not Listed
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	0.5% TO 1.5%	Not Listed
 Acetic acid, vinyl ester, polymer 	9003-20-7	< 11%	Not Listed
Glass, oxide, chemicals	65997-17-3	78% TO 97%	Not Listed
U.S Pennsylvania - RTK (Right to Know) - Special Hazardous Sub	stances		
Glass, oxide, chemicals as Glass wool fiber		78% TO 97%	Not Listed
 Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment) 	64742-65-0	0.5% TO 1.5%	Not Listed



	Acetic acid ethenyl ester, polymer with ethene	24937-78-8	< 7%	Not Listed
	Asphalt	8052-42-4	0% TO 17%	Not Listed
	Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	0.5% TO 1.5%	Not Listed
١.	Acetic acid, vinyl ester, polymer	9003-20-7	< 11%	Not Listed
١.	Glass, oxide, chemicals	65997-17-3	78% TO 97%	Not Listed

United States - Rhode Island

Labor			
U.S Rhode Island - Hazardous Substance List			
Glass, oxide, chemicals as Glass wool fiber		78% TO 97%	Toxic
 Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment) 	64742-65-0	0.5% TO 1.5%	Not Listed
 Acetic acid ethenyl ester, polymer with ethene 	24937-78-8	< 7%	Not Listed
 Asphalt 	8052-42-4	0% TO 17%	Toxic; Flammable
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	0.5% TO 1.5%	Not Listed
 Acetic acid, vinyl ester, polymer 	9003-20-7	< 11%	Not Listed
Glass, oxide, chemicals		78% TO 97%	Toxic

Additional Regulatory Information

 WARNING: This product contains a chemical known to the State of California to cause cancer.

Section 16 - Other Information

Last Revision Date Preparation Date Acronyms/Definitions **o**6/22/2012

10/15/2004

 For reference to the acronyms/definitions used in this MSDS please visit www.certainteed.com.

Disclaimer/Statement of Liability

Reasonable care has been taken in the preparation of this information, but the supplier gives no warranty of merchantability or of fitness for a particular purpose. Any product purchased is sold on the assumption the purchaser will make his own tests to determine the quality and suitability of the product. Supplier expressly disclaims any and all liability for incidental and/or consequential property damage arising out of the use of this product. No information provided shall be deemed to be a recommendation to use any product in conflict with any existing patent rights. Read the Material Safety Data Sheet before handling product.

End of CT 10144-7