

## Canadian Metal Building Insulation

### PRODUCT DESCRIPTION

**Basic Use:** Canadian Metal Building Insulation is a flexible fibre glass blanket insulation furnished in unfaced rolls. Its primary use is in exterior walls and standing seam roofing systems of pre-engineered metal buildings. It is intended to be laminated with an appropriate vapour retarder facing suited to the specific job application, and can also be used as an unfaced layer of insulation.



**Benefits:** Canadian Metal Building Insulation reduces the level of exterior and interior noise by reducing transmission of exterior sound to the interior of the building and absorbing reverberating sounds within the building. Canadian Metal Building Insulation provides thermal efficiency, helping to keep heat inside the building in winter and outside in summer. When faced with a vapour retarder it helps control condensation on the inside surfaces of the building's roof and walls.

**Composition and Materials:** The product is composed of tan, uniformly textured, inorganic fibrous glass and formed with a formaldehyde-free binding agent.

**Limitations:** This product is designed for use in interior (weather protected) walls and roofs of pre-engineered metal buildings. It should be laminated on a first-in, first-out basis and should be kept dry at all times during processing and end use. After lamination, packaging should not exceed a 5.5:1 compression ratio.

**Sizes:** Standard available sizes as noted in table on other side.

### INSTALLATION

The vapour retarder on Canadian Metal Building Insulation should be installed toward the conditioned spaces in the building. The insulation is normally applied over or between the structural members of the building and held in place by the covering sheets or insulation support system. When using high R-Value systems, it is recommended that the cavity between the exterior metal sheet and the faced fibre glass insulation should be completely filled.

### AVAILABILITY AND COST

Manufactured in the United States and Canada and sold in Canada. For availability and cost, contact your local distributor or call CertainTeed in Valley Forge, PA at 800-233-8990.

### WARRANTY

Inasmuch as CertainTeed has no control over lamination, installation design, installation workmanship, accessory materials or conditions of application, CertainTeed does not warrant the performance or results of any installation containing its products.

### MAINTENANCE

An inspection and preventative maintenance program for the insulation and vapour retarder system is recommended to ensure optimum performance.

### TECHNICAL SERVICES

Technical assistance can be obtained either from the local CertainTeed sales representative, or by calling CertainTeed in Valley Forge, PA at 800-233-8990.

<b>Product Name</b>	CertainTeed Canadian Metal Building Insulation
<b>Manufacturer</b>	CertainTeed Corporation
<b>Address</b>	P.O. Box 860 Valley Forge, PA 19482-0105
<b>Phone</b>	610-341-7000 • 800-233-8990
<b>Fax</b>	610-341-7571
<b>Website</b>	<a href="http://www.certainteed.com/insulation">www.certainteed.com/insulation</a>

### TECHNICAL DATA

#### Applicable Standards

- Material Standards:
  - CAN/ULC-S702, Type I

#### Fire Resistance

- Fire Hazard Classification:
  - CAN/ULC-S102  
Max. Flame Spread Index: 25  
Max Smoke Developed Index: 50
- Non-combustible:
  - ASTM E136 / Meets requirements

#### Physical/Chemical Properties

- Thermal Resistance:
  - ASTM C518 and/or ASTM C177 / at 75°F (24°C) mean temperature
- Acoustical Performance: See tables on other side
- Water Vapour Sorption:
  - ASTM C1104 / No greater than 5.0% by weight
- Smoulder Resistance:
  - CAN / ULC-S129 / No greater than 5.0%
- Odor Emission:
  - ASTM C1304 / Pass

#### Quality Assurance

CertainTeed's commitment to quality and environmental management has ensured the registration of the Athens, Chowchilla and Kansas City plants to ISO 9001:2000 and ISO 14001:2004 standards.



**FILING SYSTEMS**

- Additional product information available upon request.

SOUND ABSORPTION - UNFACED									
R-Value	Nom. Thickness		Absorption Coefficients @ Octave Band Frequencies (Hz)						NRC
R	in.	mm	125	250	500	1000	2000	4000	
10	3.5	89	0.29	0.82	1.02	0.94	0.96	0.98	0.95
12	3.875	98	0.39	0.91	1.01	0.92	0.93	0.98	0.95
14	4.5	114	0.53	0.97	1.04	0.90	0.95	0.98	0.95
16	5.25	133	0.67	1.05	1.02	0.92	0.98	0.99	1.00
20	6.375	162	0.89	1.22	1.02	0.98	1.01	1.00	1.05

Sound absorption tested in accordance with ASTM C423 using Type A mounting per ASTM E795.

**AVAILABLE SIZES**

R-VALUE	RSI	LABEL THICKNESS		WIDTH		LENGTH	
		in.	mm	in.	mm	1-foot increments	1-meter increments
6	1.06	2	50.8	36 – 72	914.4 – 1,828.8	50 to 110	15.24 to 33.53
10	1.76	3	76.2	36 – 72	914.4 – 1,828.8	50 to 110	15.24 to 33.53
12	2.11	3.5	88.9	36 – 72	914.4 – 1,828.8	50' to 75	15.24 to 22.86
13	2.29	4	101.6	36 – 72	914.4 – 1,828.8	25 to 50	7.62 to 15.24
14	2.47	4.5	114	36 – 72	914.4 – 1,828.8	25 to 50	7.62 to 15.24
16	2.82	5.25	133.35	36 – 72	914.4 – 1,828.8	25 to 50	7.62 to 15.24
17	3.17	5	127	36 – 72	914.4 – 1,828.8	25 to 50	7.62 to 15.24
20	3.52	6	152.4	24 – 72	609.6 – 1,828.8	25 to 50	7.62 to 15.24
25	4.40	8	203.2	36 – 72	914.4 – 1,828.8	25	7.62
26	4.58	8	203.2	36 – 72	914.4 – 1,828.8	25	7.62
28	4.93	8.5	215.9	36 – 72	914.4 – 1,828.8	25	7.62

For specific item information or made-to-order sizes contact your territory manager or customer service representative.



**ASK ABOUT ALL OF OUR OTHER CERTAINTEED® PRODUCTS AND SYSTEMS:**

ROOFING • SIDING • TRIM • DECKING • RAILING • FENCE • FOUNDATIONS  
GYPSUM • CEILINGS • INSULATION • PIPE

www.certainteed.com    http://blog.certainteed.com

CertainTeed Corporation  
P.O. Box 860  
Valley Forge, PA 19482

Professional: 800-233-8990  
Consumer: 800-782-8777

