

ELASTOCOL STICK

TECHNICAL DATA SHEET
131007SCAN9E
(supersedes 130318SCAN1E)

DESCRIPTION

ELASTOCOL STICK is a primer designed to enhance the adhesion of self-adhesive membranes on porous surfaces such as "DENS GLASS GOLD" and "DENS DECK" at temperatures above $-10\text{ }^{\circ}\text{C}$ ($14\text{ }^{\circ}\text{F}$). It is composed of SBS synthetic rubbers, adhesive enhancing resins and volatile solvents. It is also suitable to prime non-porous surfaces such as concrete, fibre cement, metal, and wood.

APPLICATION

ELASTOCOL STICK can be applied with a brush, a roll or a spray can. It must be thoroughly dry before applying the waterproofing membrane. **ELASTOCOL STICK** must be shaken well before use.

WARNING: DO NOT ACCELERATE DRYING OF ELASTOCOL STICK BY HEATING IT WITH A TORCH.
FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.

COVERAGE

Average coverage: porous surfaces: 0.3 to 0.5 L/m²,
non-porous surfaces: 0.1 to 0.25 L/m².

PROPERTIES

| Properties | ELASTOCOL STICK |
|--|--|
| Specific Gravity at 20 °C (68 °F) | 0.79 kg/L |
| Colour | Red |
| Solids by Weight | 24 % |
| Viscosity, Brookfield at 25 °C (77 °F) | 200 cP |
| Drying time | 15 to 60 minutes, depending on temperature and quantity applied. |

(All values are nominal)

PACKAGING

3.78 L, 19 L pails and 350 g spray cans.

STORAGE & HANDLING

Shelf life: Up to 60 months in original sealed containers, in cool and ventilated area.

Tools can be cleaned with petroleum solvents such as mineral spirits, varsol, xylene, etc.

Store in a well ventilated area. Keep away from any source of heat, dampness, humidity, oxidizing agents or direct sunlight. Flammable before curing. Keep away from sources of ignition.

For more information, refer to instruction on the label of the can and to relevant Material Safety Data Sheet (MSDS).