

# 1540CW

## ASJ INSULATION TAPE

Venture Tape 1540CW COLD WEATHER ASJ is a 9.7 mil (125  $\mu$ m) white kraft paper/scrim/foil (ASJ) lamination coated with Venture's CW cold weather solvent acrylic pressure sensitive adhesive. Specifically designed for use as a vapor seal on ASJ faced duct board and pipe insulation, Venture Tape 1540CW applies easily and excels in demanding temperature and humidity applications, providing superior performance and durability over a wide range of conditions. The facing used on Venture Tape 1540CW meets ASTM C1136, Type I, II, III, IV.

### Features & Benefits

Specifically designed for cold weather conditions

Name	Imperial Typical Value	Typical Value (Metric)
Thickness Carrier	9.7 mils	246.4 microns
Adhesive Thickness - Exp	1.8 mils	45.7 microns
Thickness Liner	3.1 mils	78.7 microns
Peel Adhesion - Exp	92 oz/inch width	26.6 N/25 mm
Shear Adhesion	>168 hrs	>168 hrs
Tensile Strength	40 lbs/inch width	178 N/25 mm
Elongation	2%	2%
Minimum Appl	-35 degrees F	-37 degrees C
Maximum Use Temp	300 degrees F	149 degrees C

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Contact Venture Tape today for a complete list of products or a free sample  
Toll Free North America 800-343-1076  
From United Kingdom 0-800-962-957  
From Australia 1-800-122-797  
[www.venturetape.com](http://www.venturetape.com)  
[www.boma.it](http://www.boma.it)



**USA**  
Venture Tape Corp.  
30 Commerce Road  
Rockland, MA 02370  
781-331-5900  
FAX 781-871-0065  
[www.venturetape.com](http://www.venturetape.com)

**Europe - Venture Tape**  
Venture Tape Europe Corp.  
Units 5 - 6, Faraday Close,  
Drayton Fields, Daventry,  
Northamptonshire, England NN11 8RD  
(0) 1327 876555  
FAX (0) 1327 876444

**Australasia**  
Venture Tape Australasia, Pty., Ltd.  
11B Production Drive  
Campbellfield, VIC 3061  
Australia  
(03) 9357 6025  
FAX (03) 9357 6045